



(12) **United States Patent**
Moussette et al.

(10) **Patent No.:** **US 9,535,501 B1**
(45) **Date of Patent:** **Jan. 3, 2017**

(54) **INPUT WITH HAPTIC FEEDBACK**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(72) Inventors: **Camille Moussette**, Los Gatos, CA (US); **John Morrell**, Los Gatos, CA (US); **Duncan Robert Kerr**, San Francisco, CA (US); **Benjamin G. Jackson**, Belmont, CA (US); **Steven J. Taylor**, San Jose, CA (US)

(73) Assignee: **APPLE INC.**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/974,606**

(22) Filed: **Dec. 18, 2015**

Related U.S. Application Data

(63) Continuation of application No. 14/745,416, filed on Jun. 29, 2015.

(51) **Int. Cl.**
G06F 3/041 (2006.01)
G06F 3/01 (2006.01)

(52) **U.S. Cl.**
CPC **G06F 3/016** (2013.01); **G06F 3/041** (2013.01)

(58) **Field of Classification Search**
CPC G06F 3/016; G06F 3/03; G06F 3/0362; G06F 3/046; G06F 3/048; G06F 3/0488
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,304,133 A * 12/1981 Feamster, III B23Q 1/621 73/633
5,483,261 A 1/1996 Yasutake

5,488,204 A 1/1996 Mead et al.
5,587,937 A * 12/1996 Massie B25J 9/1689 700/264
5,709,219 A * 1/1998 Chen A63F 13/06 345/156

(Continued)

FOREIGN PATENT DOCUMENTS

JP 2000-163031 A 6/2000
JP 2002-342033 A 11/2002
WO WO-2014/200766 A1 12/2014

OTHER PUBLICATIONS

Lee, S.K. et al. (Apr. 1985). "A Multi-Touch Three Dimensional Touch-Sensitive Tablet," *Proceedings of CHI: ACM Conference on Human Factors in Computing Systems*, pp. 21-25.

(Continued)

Primary Examiner — Joe H Cheng

(74) *Attorney, Agent, or Firm* — Morrison & Foerster LLP

(57) **ABSTRACT**

An electronic device is disclosed. The electronic device includes a mechanical input configured to move in a first direction in response to an input at the mechanical input. A mechanical input sensor is coupled to the mechanical input and configured to sense the input at the mechanical input based on the movement of the mechanical input in the first direction. A mechanical input actuator is coupled to the mechanical input and configured to displace the mechanical input in a second direction, different from the first direction. In some examples, the second direction is orthogonal to the first direction. In some examples, the mechanical input comprises a rotary input configured to rotate in the first direction in response to the input. In some examples, the mechanical input actuator is configured to displace the mechanical input in the second direction while the mechanical input is moving in the first direction.

19 Claims, 7 Drawing Sheets

